

DTD documentation

1. Top-level element(s)

- [document](#)

2. List of elements

- [abstract](#)
- [acronym](#)
- [anchor](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [em](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [fork](#)
- [header](#)
- [icon](#)
- [img](#)
- [jump](#)
- [legal](#)
- [li](#)
- [link](#)
- [note](#)
- [notice](#)
- [ol](#)
- [p](#)
- [person](#)

- [section](#)
- [source](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

3. Element declarations

3.1.

person		
Content model		EMPTY
Attributes		
	id	
	xml:lang	
	name	
	email	
Used inside	authors	

3.2.

strong	
Content model	(#PCDATA code) *

Attributes	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal	

3.3.

em		
Content model	(#PCDATA code) *	
Attributes	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal	

3.4.

code		
Content model	(#PCDATA)	
Attributes	id	
	xml:lang	
Used inside	strong em link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal	

3.5.

sup		
Content model	(#PCDATA)	
Attributes	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal	

3.6.

sub		
Content model	(#PCDATA)	
Attributes	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd title subtitle notice abstract legal	

3.7.

link		
Content model	(#PCDATA strong em code sub sup br img icon acronym) *	
Attributes	id	
	xml:lang	

	href	
	role	
	title	
Used inside	p source note warning fixme caption th td li dt dd notice abstract legal	

3.8.

jump		
Content model	(#PCDATA strong em code sub sup br img icon acronym) *	
Attributes	id	
	xml:lang	
	href	
	role	
	title	
Used inside	p source note warning fixme caption th td li dt dd notice abstract legal	

3.9.

fork		
Content model	(#PCDATA strong em code sub sup br img icon acronym) *	
Attributes	id	
	xml:lang	
	href	

	role	
	title	
Used inside	p source note warning fixme caption th td li dt dd notice abstract legal	

3.10.

br		
Content model	EMPTY	
Attributes	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd notice abstract legal	

3.11.

img		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	
	usemap	
	ismap	

	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd notice abstract legal	

3.12.

icon		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	
	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd notice abstract legal	

3.13.

acronym		
Content model	(#PCDATA) *	
Attributes	title	

	id	
	xml:lang	
Used inside	link jump fork p source note warning fixme caption th td li dt dd notice abstract legal	

3.14.

p		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
	xml:space	
Used inside	body section	

3.15.

source		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes		
	id	
	xml:lang	
	xml:space	

Used inside	body section

3.16.

note	
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *
Attributes	id
	xml:lang
Used inside	body section

3.17.

warning	
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *
Attributes	id
	xml:lang
Used inside	body section

3.18.

fixme	
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *
Attributes	author

	id	
	xml:lang	
Used inside	body section	

3.19.

table		
Content model	(caption ? , tr +)	
Attributes	id	
	xml:lang	
Used inside	body section	

3.20.

caption		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
Used inside	table	

3.21.

tr	
Content model	(th td) +

Attributes	id	
	xml:lang	
Used inside	table	

3.22.

th		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
	colspan	
	rowspan	
Used inside	tr	

3.23.

td		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
	colspan	
	rowspan	

Used inside	tr

3.24.

li					
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork ol ul dl) *				
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	ul ol				

3.25.

ul							
Content model	(li ol ul dl) +						
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> <tr> <td>spacing</td><td></td></tr> </table>	id		xml:lang		spacing	
id							
xml:lang							
spacing							
Used inside	li ul ol body section						

3.26.

ol

Content model	(li ol ul dl) +	
Attributes		
	id	
	xml:lang	
	spacing	
Used inside	li ul ol body section	

3.27.

dl		
Content model	(dt , dd) +	
Attributes	id	
	xml:lang	
Used inside	li ul ol body section	

3.28.

dt		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
Used inside	dl	

3.29.

dd		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes		
	id	
	xml:lang	
Used inside	dl	

3.30.

figure		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	
	usemap	
	ismap	
	id	
	xml:lang	
Used inside	body section	

3.31.

anchor		
Content model	EMPTY	
Attributes	id	
	xml:lang	
Used inside	body section	

3.32.

document		
Content model		(header , body , footer ?)
Attributes	id	
	xml:lang	

3.33.

header		
Content model	(title , subtitle ? , version ? , type ? , authors ? , notice * , abstract ?)	
Attributes	id	
	xml:lang	
Used inside	document	

3.34.

title		
Content model	(#PCDATA strong em code sub sup) *	
Attributes	id	
	xml:lang	
Used inside	header section	

3.35.

subtitle		
Content model	(#PCDATA strong em code sub sup) *	
Attributes	id	
	xml:lang	
Used inside	header	

3.36.

version		
Content model	(#PCDATA)	
Attributes	id	
	xml:lang	
	major	
	minor	
	fix	

	tag
Used inside	header

3.37.

type					
Content model	(#PCDATA)				
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	header				

3.38.

authors					
Content model	(person +)				
Attributes	<table> <tr> <td>id</td><td></td></tr> <tr> <td>xml:lang</td><td></td></tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	header				

3.39.

notice	
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *

Attributes	id	
	xml:lang	
Used inside	header	

3.40.

abstract		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
Used inside	header	

3.41.

body		
Content model	(section p source note warning fixme table ol ul dl figure anchor) +	
Attributes	id	
	xml:lang	
Used inside	document	

3.42.

section

Content model	(title , (section p source note warning fixme table ol ul dl figure anchor) *)	
Attributes	id	
	xml:lang	
Used inside	body section	

3.43.

footer	
Content model	(legal)
Used inside	document

3.44.

legal		
Content model	(#PCDATA strong em code sub sup br img icon acronym link jump fork) *	
Attributes	id	
	xml:lang	
Used inside	footer	